


**Features:**



**Application:**

**Absolute Maximum Ratings( 2 ° )**

Symbol	Parameter	Value	Unit
		100	
		100	
( )	, 120°C	( ) 10( )	
	, .3	100	
		1 0	°
		- +1 0	°

**Thermal Characteristics( 2 ° )**


Symbol	Parameter	Max	Unit
	,	2.	° /
	,	10	° /

**Electrical Characteristics( 2 ° )**


Symbol	Parameter	Test Conditions	Min	Max	Unit
		100	100		
	100	2 °		0.1	
	100	12 °			
		2 °	0.		
		12 °	0.		
	10	2 °	0.		
	10	12 °	0.		

## Typical Performance Characteristics


**Figure 1. Forward Current Characteristics**




**Figure 2. Reverse Leakage Current**



**Figure 3. Junction Capacitance**



**Figure 4. Power Derating**



### TO-220 MECHANICAL DATA

	.00		. 0		. 0	10. 0
	1.1		1.		2.	
1	0. 0		1. 0		1.10	1. 0
1	0.		0.		12. 0	1 . 0
	0.30		0. 0	1	2. 0	3. 0
	1 . 0		1 . 0		2. 0	3.10
1	. 0		. 0	1	2.00	3.00
					3. 0	.00

