

SB4040S 40A SCRs

FEATURES


- High thermal cycling performance
- High voltage capacity
- Very high current surge capability

APPLICATIONS

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Parameters Summary

VD/VR:1200V/1600V, IT(RMS):400A, UAT:400mA



ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T _{stg}	-40~150	°C
Operating junction temperature range	T _j	-40~125	°C
Repetitive peak off-state voltage	V _{DRM}	1200/1600	V
Repetitive peak reverse voltage	V _{RRM}	1200/1600	V
Non repetitive surge peak Off-state voltage	V _{DSM}	V _{DRM} +100	V
Non repetitive peak reverse voltage	V _{RSM}	V _{RRM} +100	V
Non repetitive surge peak on-state current	I _{TSM}	420	A
RMS on-state current (180° conduction angle)	I _{T(RMS)}	40	A
Average on-state current (180° conduction angle)	I _{TAV}	25	A
I ² t value for fusing (tp=10ms)	I ² t	880	A ² S
Critical rate of rise of on-state current (I=2×IGT, tr≤100 ns)	di/dt	150	A/μS
Peak gate current	IGM	4	A
Peak gate power	PGM	5	W

Thermal Resistances

Symbol	Parameter		Value	Unit
R _{th(j-c)}	Junction to case (DC)	TO-220A	1.2	°C/W
		TO-220C	0.8	°C/W
		TO-3P	0.7	°C/W

Electrical Characteristics (at $T = 25^\circ\text{C}$, unless otherwise specified)	
Symbol	Parameter
I_{GT}	$I_{G} = 1.2I_{GT}$
V_{DOL}	$V_D = 1200\text{V}$
I_L	$I_G = 1.2I_{GT}$
I_{DRM}	$I_{DOL} = 60\text{A}$
dV/dt	$V_D = 1200\text{V}$ at $t = 12\mu\text{s}$, $T = 25^\circ\text{C}$

Mechanical Data	
Symbol	Parameter
V_{DM}	$ITM = 60\text{A}$ tp=380μs
I_{DRM}	$I_{DOL} = 60\text{A}$
I_{DPM}	$I_{DOL} = 60\text{A}$ $V_D = V_{DOL}$, $V_A = V_{AV}$

Ordering Information Scheme

SB 40 40 - 12 C S


Standard SCR series
A:TO-220A C:TO-220C
M:TO-3P

IT(RMS):40A

IGT:40mA


VD/VR:1200/1600V

TO-220A Package Mechanical Data




	Dimensions	Millimeters	Inches
H	Height	11.5	0.453
L1	Lead length	1.5	0.059
L2	Lead spacing	4.4	0.173
L3	Lead thickness	0.8	0.031
E	Case width	10.5	0.413
C2	Case height	3.8	0.150
C3	Case thickness	0.8	0.031
C	Case width	10.5	0.413
A	Lead thickness	0.8	0.031
D	Lead thickness	0.8	0.031
F	Lead thickness	0.8	0.031
G	Lead thickness	0.8	0.031

TO-220C Package Mechanical Data



Ref.	Dimensions				
	Millimeters			Inches	
	Min.	Typ.	Max.	Min.	Max.
A	4.40		4.60	0.173	0.181
B	0.70		0.90	0.028	0.035
C	0.45		0.60	0.018	0.024
C2	1.30		1.48	0.048	0.052
C3	2.20		2.60	0.087	0.102
D	9.00		9.35	0.354	0.390
E	9.00		10.3	0.390	0.406
F	6.30		6.90	0.248	0.272
G		2.54			0.1
H	28.0		29.8	1.102	1.173
L1		3.39			0.133
L2	1.14		1.70	0.045	0.067
L3	2.65		2.95	0.104	0.116
e		3.6			0.142

TO-3P Package Mechanical Data



Ref.	Dimensions				
	Millimeters			Inches	
	Min.	Typ.	Max.	Min.	Max.
A	4.40		4.60	0.173	0.181
B	1.40		1.60	0.055	0.062
C	15.48		15.88	0.609	0.625
C2	0.50		0.70	0.019	0.027
C3	2.70		2.90	0.106	0.114
D	15.15		16.32	0.600	0.642
E	20.27		20.67	0.798	0.815
F	15.15		15.35	0.590	0.597
G		5.45			0.214
H	1.10		1.30	0.043	0.051
L1	1.15		1.35	0.045	0.053
L2	2.68		3.08	0.105	0.121
L3		4.20			0.165
e	4.40		4.60	0.173	0.181

FIG.1 Maximum power dissipation versus on-state current




FIG.3: Surge peak on-state current versus number of cycles




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$, and corresponding value of $|dI/dt| < 50\text{A}/\mu\text{s}$




FIG.2: on-state current versus case temperature




FIG.4: On-state characteristics (maximum values)




FIG.6: Relative variations of gate trigger current holding current and latching current versus junction temperature

