




### Pin Configuration



SOP-7

### Marking information



SOP-7

DP2701X for product name:

The third and fourth X on behalf of the date of shipment. The last two X represent the

### Typical Power Tab Power

Output Voltage	Output Current	Output Power
1.2V	10A	12W
1.5V	8A	12W
2.0V	6A	12W
2.5V	5A	12.5W
3.0V	4A	12W
3.3V	3.6A	11.88W
4.0V	3A	12W
5.0V	2.4A	12W
6.0V	2A	12W
7.0V	1.7A	11.9W
8.0V	1.5A	12W
9.0V	1.3A	11.7W
10.0V	1.2A	12W
12.0V	1.0A	12W
15.0V	0.8A	12W
20.0V	0.6A	12W
25.0V	0.48A	12W
30.0V	0.4A	12W
35.0V	0.34A	11.9W
40.0V	0.3A	12W
45.0V	0.27A	12.15W
50.0V	0.24A	12W
60.0V	0.2A	12W
70.0V	0.17A	11.9W
80.0V	0.15A	12W
90.0V	0.13A	11.7W
100.0V	0.12A	12W

Note 1. The Max. output power is limited by junction temperature.

Note 2. 230VAC or 100V/115VAC with 50% duty cycle.

Note 3. Typical continuous power in a non-ventilated enclosed adapter with sufficient drain pattern as a heat sink at 50°C ambient.

